

P.ta IVA Cod. Fisc. IT00227730181 Via 4 Novembre 40 27036 Mortara (PV) Tel.: +39 0384 00 200

P.ta IVA Cod. Fisc. IT00227730181 Via 4 Novembre, 18 27036 Mortara (PV)
Tel.: +39 0384 98 333 Fax.: +39 0384 98 389
e-mail: info@zincocofani.it

SAFETY DATA SHEET	Page 1 of 5
	Issued: 28.08.2008
Product name: SOFT ZINC	Date of revision:
	Number of revision:

1. Product and company identification:									
1.1.	Product name:		SOFT ZINC		Ident. Nr.: P30104				
						Department: Metalurgija			
1.2.	Application:			Tinsmith p	roducts				
1.3.	Supplier data (ma	anufactu	rer,	importer, o	distributor):				
1.3.1.	Name:			CINKARN	A CELJE, d.d.				
1.3.2.	Address and tele number:	phone		Kidričeva 26, 3001 CELJE – SLOVENIJA, +386 (0)3 3427 6000					
1.3.4.	Emergency telep number:	hone		+386 (0)3-3427 6184					
2. Coi	mposition / inf	format	ion	on ingr	edients:				
2.1	Common chemic	al name:							
2.2.	Hazardous comp	onents:		none					
Chemical	name:	Index	CA	S number.	EC number	Conc.(wt.%)	Hazard labellin	g R - phrases	S - phrases
3. Haz	ards identific	ation:							
3.1	Hazard:			This product is not a hazardous substance.					
3.2.	Specific hazards:			By contact with acids or alkaloids is coming to a chemical reaction, by which the hydrogen gas arises. By warming up over 650°C, ZnO gas exhales.					
3.3.	3. Main symptoms:			Exposure to ZnO gas can cause coughing, weakness and headache. This trouble will disappear in 1 – 2 days.					
4. First-aid measures:									
4.1	4.1 General instructions:			Measures are necessary only by inhalation of zinc oxides or dust or by scald with melted zinc. The injured person must be taken to fresh air, get medical attention.					
4.2.	Inhalation:			Provide fre	esh air. In case	of special syn	nptoms, seek n	nedical assistance.	

Cinkarna Celje, SAFETY DATA SHEET	Page 2 of 5
Product name: SOFT ZINC	

4.3.	Skin contact:	By burning skin washing out the wound with fresh water, get medical attention.		
4.4.	Eye / mucous membrane contact:	Flush eyes with large amounts of water. If irritation persists, get medical attention.		
4.5.	Inquisition:	By weakness inhale fresh air. Get medical attention.		
4.6.	First aid at worksite:	Provide fresh air. Rinse with water.		
5. Fire	e-fighting measures:			
5.1.	Extinguishing media:	By surrounding fire no limits. Fire as result of melted zinc must be extinguished with sand or special means of class D. Water and CO ₂ are not permitted.		
5.2.	Specific hazards:	Explosion, widening of fire by extinguishing with water.		
5.3.	Protection equipment:	Protective mask, helmet, fire safe clothes and gloves.		
6. Acc	ident outflow measure	es es		
6.1.	Personal precautions:	Zinc sheet is a solid substance, outflow is not possible.		
6.2.	Environmental precautions:			
6.3.	Methods for cleaning up:			
7. Han	7. Handling and storage			
7.1.	Handling:	Special attention to sharp edges and slippery plates.		
7.1.1.	Precautions:	Protective clothes and gloves.		
7.1.2.	Technical measures:	Protection of packaging with binding bands and protecting paper.		
7.1.3.	Safe handling advise:	Use shears for bands cutting, unwinding device by unpacking.		
7.2.	Storage:	In a dry and ventilated storage.		
7.2.1.	Safety storage conditions:	Original packaging, in a dry and ventilated storage.		
7.2.2.	Incompatible products to separate:	Acids and alkaloids.		
7.2.3.	Packaging demands:	Protective paper, transporting pallet.		
7.2.4.	Protection against static electricity:	Protective paper, transporting wood pallet.		
8. Exp	8. Exposure controls / personal protection			
8.1.	Technical measures:	Generally technical safety measures for sheet remaking, roofer's and tinsmith's trade.		
8.2.	Control parameters:	Weather conditions by sheet remaking, roofer's and tinsmith's works.		

Cinkarna Celje, SAFETY DATA SHEET	Page 3 of 5
Product name: SOFT ZINC	

8.3.	Personal protection equipment:	Protective clothes, gloves, cap, shoes and glasses.		
0.0.4		Vantilated room		
8.3.1.	Respiratory organ protection :	Ventilated room.		
8.3.2.	Skin and body protection:	Protective work clothing.		
8.3.3.	Hand protection:	Protective gloves.		
8.3.4.	Eye protection:	Glasses.		
8.3.5.	Hygiene measures:	The usual precautionary measures for handling with sheets.		
9. Phy	sical and chemical pro	operties:		
9.1.	Form:	Metallic plates, silver colour, after exposing on atmosphere the surface will be patinated.		
9.2.	Odour:	without		
9.3.	pH - Value:	1		
9.4.	Melting point / range:	419°C		
9.5.	Boiling point / range:	906°C		
9.6.	Flash point:	1		
9.7.	Inflammability:	Near the boiling point.		
9.8.	Autoignition temperature:	Near the boiling point		
9.9.	Explosion properties:	Possible by contact of melted zinc and water.		
9.10.	Oxidising properties:	Possible in the presence of damp.		
9.11.	Vapour pressure:	1.33 kPa by 487°C		
9.12.	Density:	7200 kg/m ³		
9.13.	Solubility :	Insoluble		
9.14.	Partition coefficient:	1		
9.15.	Other information:	1		
9.16.	Note:	1		
10. st	10. stability and reactivity:			
10.1.	Stability and reactivity:	Stable under recommended storage conditions, reactive in contact with acids and alkaloids.		
10.1.1.	Conditions to avoid:	Storage in a damped room.		

Cinkarna Celje, SAFETY DATA SHEET	Page 4 of 5
Product name: SOFT ZINC	

10.1.2.	Materials to avoid:	Sourness, alkaloids, damp, cooper and iron.			
10.2.	Hazardous decomposition products:	Zinc oxides by melting.			
10.3.	Other information:	Recrystallisation at 320°C.			
11. To	oxicological information				
11.1.	Acute toxicity:	none			
11.2.	Chronic toxicity; long term toxicity:	none			
11.3.	Sensitisation:	none			
11.4.	Specific effects:	none			
12. Ed	cological information:				
12.1.	Mobility:	Low : - 0.01 mm thickness / year			
12.2.	Degradability:	If they are not regularly mounted, zinc sheets can disintegrate to zinc hydroxide.			
12.3.	Bioaccumulation:	Not expected to accumulate in biological organisms.			
12.4.	Ecotoxicity	none			
12.5.	Other negative effects on the environment:	none			
13. Di	sposal considerations:				
13.1.	Product:	Zinc can be remade in totality by the normal production process.			
13.2.	Contaminated packaging:	Packaging is not contaminated. The palettes and paper can be burned out, the banding binds remade in steelworks.			
14. Tr	14. Transport information:				
14.1.	Land (RID,ADR, CFR):	Not classified			
14.2.	UN number:	1			
14.3.	Product / goods designation:				
14.4.	Product / goods class:	1			
14.5.	Classification cods:				
14.6.	Substance packaging group:				
14.7.	Hazard label:				
	•				

Cinkarna Celje, SAFETY DATA SHEET	Page 5 of 5
Product name: SOFT ZINC	

15. Regulatory information:			
15.1.	EC classification, letter-symbol, hazard inscriptions, S and R (including text), special, regulations:		
15.1.1.	Classification:		
15.1.2.	Indication:		
15.1.3.	Warnings:		
15.1.4.	Notices:		
15.1.5.	Special provisions:		
15.2.	Possible existence of local regulations:	Official gazette of Republic Slovenia, No. 101/02.	
16. Of	16. Other information:		
16.1.	Workers qualifying :	Suitable education for tinsmiths or roofer, examination for work protection.	
16.2.	Recommended use and possible restrictions:	Tinsmiths products	
16.3.	Instructions:	Technical instructions by producer.	
16.4.	Sources :	Official gazette of Republic Slovenia, Nr. 73/1999, 101/02, EN 1179	

The information is based on our knowledge of the product at the time of compilation of this safety data sheet. If the product is used in a way that is not compliant with the recommended use, the user / buyer shall solely be held responsible for any resulting damage. Furthermore, the information in this safety data sheet does not relieve the user of any obligation to comply with all legislation relevant for the field of the users' activity.